

GARDENING RANGE



2T Technosynthese®

Garden 2T Hi-Tech 1

Technosynthese® based high performance lubricant. Specially formulated for 2-Stroke engines of gardening power equipment. Recommended for engines working under severe conditions or at high engine speeds.

■ Standards ISO L-EGD, JASO FD, API TC

Garden 2T

Technosynthese® based lubricant. Specially formulated for 2-Stroke engines of gardening power equipment. Recommended for engines working under severe conditions or at high engine speeds.

■ Standards API TC



4T Technosynthese®

Garden 4T 10W30

Technosynthese® based lubricant. Specially formulated for small farming power equipment. For all petrol and Diesel 4-Stroke engines, naturally aspirated or turbocharged. Performance level for Honda.

■ Standards API SJ / CF

4T Mineral

Garden 4T 15W40

Specially formulated for small farming power equipment. For all petrol and Diesel 4-Stroke engines, naturally aspirated or turbocharged.

■ Standards API SG / CD

Garden 4T SAE 30 2

Formulated for small farming power equipment. For all petrol and Diesel 4-Stroke engines.

■ Standards API SG / CD



Mineral

Timber 120 3

Specially formulated for the lubrication of power chain saws. For all types of power chain saws with manual or automatic lubrication systems. Appropriate viscosity for efficient lubrication while avoiding risks of oil splashes. Fluid enough but highly adhesive.



Timber 150

Specially formulated for the lubrication of power chain saws used by professionals. For all types of power chain saws with manual or automatic lubrication systems.



Biodegradable

Timber Bio

1



For all types of power chain saws with manual or automatic lubrication systems. 100% biodegradable. Fluid and adhesive. Meets the specifications of the German Ministry of Ecology.

- **Approvals** European Ecolabel: DE/027/016, Der Blaue Engel: UZ 48



1

2T

Bio 2T

2

Developed for 2-stroke engines running in severe conditions. Based on complex Ester with very high combustion power for a drastic reduction of smoke and deposits. 80% biodegradable.

- **Standards** API TC / ISO-L-EGC
- **Approvals** JASO FC: under number 033MOT011
- **Biodegradability** CEC L-33-A-93



2

Rubric Bio 46 S

Biodegradable hydraulic fluid based on high performance saturated Ester. 100% Synthetic. Specially developed for hydraulic systems working under severe conditions.

- **Standards** ISO 15380 HEES
- **Approvals** European Ecolabel: UK/27/006, Bosch Rexroth: RE 902221-01

Rubric Bio 46

Biodegradable hydraulic fluid, 100% synthetic, with anti-oxidation, anti-wear and anti-corrosion properties under severe conditions. ISO VG 46. Biodegradability over 90% according to CEC L-33-A-93 and 89% on ISO 9439.

- **Approvals** European Ecolabel: DE/027/027, Der Blaue Engel: 18724, Bosch Rexroth: RE 902221-01



Mineral

Rubric HV 46 Ambient

Anti-wear hydraulic fluid. Very high viscosity index. ISO VG 46

- **Standards** NFE 48 602 HV / 605 HV, DIN 51 524 HVLP, DENISON HF-0, CINCINNATI MILACRON P 70, CASE POCLAIN P 110 32-03J, VICKERS V 104 C / 35 VQ 25, ISO III58 Category HV, ISO 6743-4 Category HV

Rubric HM 32 / 46 / 68

For all types of hydraulic systems.

3 viscosity grades: ISO VG 32 / VG 46 / VG 68

- **Performances** NFE 48 603 HM, DIN 51 524 HLP, DENISON HF-0, CINCINNATI MILACRON P 70, VICKERS V 104 C / 35 VQ 25



Carbu Clean 1

Carburettor cleaner: eliminates deposits and varnish on throttle valves, bushels, jets, tanks, floats, venturis. Stabilises the idle and improves engine acceleration. 400ml

E.Z. Lube 2

Multipurpose fluid lubricant: unblocks, lubricates and protects from corrosion all metal parts by depositing a protective film. 400ml

Valve Expert 3

Lead substitute additive for engines requiring leaded petrol. 250ml

Stabilizer 4

Gasoline conservation additive protecting petrol from oxidation (winter storage, occasional use). 250ml

Fuel System Clean 5

Add to the fuel for higher engine performances. Strengthened action on valves, carburetors, injectors and combustion chambers. 75ml or 200ml

Tech Grease 300 6

Very high performance multipurpose grease. Technosynthese® formulation based on complex lithium soap, with Extreme Pressure, anti-wear, anti-oxidation and anti-corrosion additives. Excellent performance at high temperature. Long life duration, water resistant. Consistency **NLGI 2**. 200g



4T 100% Synthetic

Power Quad 4T 10W40 7

Formula reinforced with Ester base stock for its synergy with anti-wear additives and improved shear resistance. Increases gears protection and life. 100% synthetic lubricant for improved oil film resistance at high temperatures.

- Standards **API SL**
- Approvals **JASO MA: under number M033MOT068**




4T Mineral

Quad 4T 10W40

Specially developed for 4-Stroke ATV engines.

- Standards **API SJ**
- Approvals **JASO MA: under number M033MOT067**



MOTUL

119 Bd Félix Faure - 93300 Aubervilliers FRANCE
 Tel. +33 (0)1 48 11 70 00 ■ Fax. +33 (0)1 48 33 28 79
 Contact: info@motul.com ■ www.motul.com